






X  
 SETH-1  
 XXXXXX  
 XX/XX  


NAME PLATE

MODEL	D	SLOPE	W	L	T	E	WEIGHT
SETH-12-3	12"	3:1	1'-10"	3'-3"	5"	12"	1,680
SETH-12-4	12"	4:1	1'-10"	4'-4"	5"	12"	2,040
SETH-12-6	12"	6:1	1'-10"	8'-0"	5"	12"	2,760
SETH-15-3	15"	3:1	2'-1¼"	4'-0"	5"	12"	1,680
SETH-15-4	15"	4:1	2'-1¼"	5'-4"	5"	12"	2,040
SETH-15-6	15"	6:1	2'-1¼"	8'-0"	5"	12"	2,760
SETH-18-3	18"	3:1	2'-5¼"	4'-9"	5"	12"	2,120
SETH-18-4	18"	4:1	2'-5¼"	6'-4"	5"	12"	2,600
SETH-18-6	18"	6:1	2'-5¼"	9'-6"	5"	12"	3,560
SETH-24-3	24"	3:1	2'-11½"	6'-3"	5"	12"	3,120
SETH-24-4	24"	4:1	2'-11½"	8'-4"	5"	12"	3,880
SETH-24-6	24"	6:1	2'-11½"	12'-6"	5"	12"	5,400
SETH-30-3	30"	3:1	3'-5¼"	7'-9"	5"	12"	4,280
SETH-30-4	30"	4:1	3'-5¼"	10'-4"	5"	12"	5,400
SETH-30-6	30"	6:1	3'-5¼"	15'-6"	5"	12"	7,600
SETH-36-3	36"	3:1	4'-3"	10'-0"	6"	12"	6,200
SETH-36-4	36"	4:1	4'-3"	12'-0"	6"	12"	9,040
SETH-36-6	36"	6:1	4'-3"	18'-3"	6"	12"	13,000



- NOTES:**
1. CLASS "C" CONCRETE
  2. 12" ARE MADE WITH 12" KNOCK OUT FOR SMALLER PIPE IN 15" SET MOLD
  3. 6" WALL IN 36" AS PER CHART
  4. REINFORCEMENT:  
 12"-24" #4 BARS @ 9" % GRADE 60  
 24"-36" #4 BARS @ 6" % GRADE 60

